

22 AWG - Stranded Tinned Copper - S-R PVC

Paired - 300 Volt - 80°C
Overall Aluminum Shield
S-R PVC Insulation

Security and Alarm Cable

Image Coming Soon

Category Conductor Description:

- Stranded tinned copper

Category Insulation Description:

- Semi-rigid Polyvinyl Chloride (S-R PVC)

Shield:

- Aluminum/polyester shield with a stranded tinned copper drain wire

Category Jacket Description:

- Gray, Polyvinyl Chloride (PVC)

Applications:

- Paired cables allow balanced signal transmission which results in lower crosstalk through common mode rejection
- The twisted pairs generally permit higher data speeds than multi-conductor cables

Standards:

- NEC CMR
- CEC CMR
- Voltage: 300 Volt

PART NUMBER TABLE

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
D52201	22	1	7x30 TC	0.01	0.035	0.177	15
D52201-BW	22	1	7x30 TC	0.013	0.035	0.186	18
D52202	22	2	7x30 TC	0.01	0.032	0.236	29.1
D52203	22	3	7x30 TC	0.01	0.032	0.25	36.3
D52204	22	4	7x30 TC	0.01	0.032	0.27	43.8

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC