

## 24 AWG – 7x32 Stranded Tinned Copper – Polyethylene

Paired - 300 Volt - 80°C  
Overall Foil/Braid Shield  
Low Capacitance for RS-485

Montrose



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Stranded tinned copper

### Category Insulation Description:

---

- Polyethylene (PE), twisted pairs

### Shield Drain:

---

- Overall aluminum-polyester shield with a tinned copper drain wire  
Overall tinned copper braid shield (90% coverage)

### Category Jacket Description:

---

- Gray, Polyvinyl Chloride (PVC)

### Applications:

---

- Allow balanced signal transmission which results in lower crosstalk through common mode rejection
- Permits higher data speeds than multi-conductor cables

### Standards:

---

- NEC CM CEC CM UL Listed: 80°C Voltage: 300 Volt

**PART NUMBER TABLE**

<b>Part#</b>	<b>Gauge</b>	<b>Pairs</b>	<b>Stranding</b>	<b>Outside Diameter Inches</b>	<b>Nominal Capacitance A</b>	<b>Nominal Capacitance B</b>	<b>Material Weight (Lbs./M')</b>
D882401	24	1	7x32 TC	0.232	12	23	30
D882402	24	2	7x32 TC	0.346	12	23	49
D882403	24	3	7x32 TC	0.36	12	23	67
D882404	24	4	7x32 TC	0.39	12	23	81

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •**  
**Seattle • St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**