

24 AWG = 7x32 Stranded Tinned Copper -
Low-Smoke PVC Jacket

**Stranded Tinned Copper
Twisted Pairs
Low-Smoke PVC Jacket**

Security and Alarm Cable

Image Coming Soon

Category Conductor Description:

- Stranded tinned copper with overall foil shield

Category Insulation Description:

- Foam Fluoropolymer

Shield Drain:

- Individual aluminum/polyester foil shield with 100% coverage

Category Jacket Description:

- Orange, low-smoke Polyvinyl Chloride (PVC)

Applications:

- Used for computers, communications, instrumentation, sound, control, audio, and data transmissions
- Designed to protect signal integrity under critical conditions by reducing noise
- Features include low dielectric constant and a dissipation factor for high speed, low distortion data handling
- Physical properties include good crush resistance and light weight

Standards:

- CMP/CL2P
- 75°C temperature rating

PART NUMBER TABLE

Part#	Gauge	Pairs	Stranding	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Nominal Capacitance	Material Weight (Lbs./M')
G62401	24	1	7x32	0.015	0.014	0.134	11.8 pF/ft.	11.3

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC