

2.4kV – Nonshielded, XLP

XLPE Insulation
2.4kV - MV-90-Dry Use - Non-shielded
Single Conductor



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Soft annealed uncoated copper Class B stranding

Category Insulation Description:

- Black thermoset XLPE

Standards:

- ICEA S-96-659
- NEMA WC-71
- UL 1072

Conductor Shield:

- Extruded semi-conducting layer

Applications:

- Suitable for use in dry locations at continuous conductor temperature of 90°C
- May be installed in conduit, duct, or properly supported aerial installations

Part Number Table

Part#	Gauge	Stranding	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
MVX10201	2	7	0.11	0.55	281
MVX14/001	4/0	19	0.11	0.78	774

*Sizes 8, 6, and 4 to be used as Airport Lighting Cable under FAA Regulation L824-C Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC