

48 CHANNEL RM – Series – Round Messenger Cables

Fiber:

- SLS, Single-mode ITU-T G.652.D

Category Description:

- Round Messenger Cables

Applications:

- Indoor/Outdoor tight-bound tight-buffered design allows cables to be installed in intra-building backbone and inter-building campus
- locations without costly transitions between cable types
- Ideal configuration for a single termination point requiring multiple fibers

Category Jacket Description:

- Black Hard Elastomeric, Polyolefin

Unit Of Measure:

- per 1000 ft

Standards:

- Optical Cable Corporation's Indoor/Outdoor tightbuffered
- fiber optic cables meet the functional
- requirements of the following standards:
 - UL 1651
 - UL 1666
 - GR-409-CORE
 - ICEA-S-104-696
 - ICEA-S-83-596
 - TIA-568
 - TIA-598
- UL-listed type OFNR in accordance with
- NEC sections 770-179 (B) and 770-154 (B)
- for use in vertical runs in building riser shafts
- or from floor to floor. Meets or exceeds
- requirements for intra-building fiber optic
- cables as outlined in GR-409-CORE.

Part Number Table

Part#	Fiber Count	Material Weight (Lbs./M')	Max Tensile Load In Service
RM048XSLS5K	12	79	2,880
RM012XSLS5K	48	47	2,880

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC