

600V - AIA - Individual and Overall Shield

Aluminum Interlocked Armor
Individual and Overall Shield
90°C - 600 Volt



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Bare copper, per ASTM Class B

Category Insulation Description:

- Cross-linked Polyethylene (XLPE) Color Code: M1, E1

Category Assembly Description:

- Pair or triad twisted with a drain wire and Aluminum/Mylar shield overall - Pairs are cabled together with a drain wire and Aluminum/Mylar shield overall

Inner Jacket:

- Black Polyvinylchloride (PVC)

Armor:

- Interlocked aluminum armor

Outer Jacket:

- Black Polyvinylchloride (PVC)

Applications:

- UL approved for direct burial
- Sunlight and oil Resistant
- Rated for CT use
- Suitable for use in Class I Division II hazardous locations

Standards:

- UL listed as Type MC, per UL Standard 1569 for metal clad cables
- Meets UL 1581, 1202, & ICEA T-29-520
- RoHS Compliant

Color Code Chart	
# of Pairs	Color
1	Black, White & Numbered
2	Black, White & Numbered
3	Black, White & Numbered
4	Black, White & Numbered
5	Black, White & Numbered
6	Black, White & Numbered

7	Black, White & Numbered
8	Black, White & Numbered
9	Black, White & Numbered
10	Black, White & Numbered
11	Black, White & Numbered
12	Black, White & Numbered
13	Black, White & Numbered
14	Black, White & Numbered
15	Black, White & Numbered
16	Black, White & Numbered
17	Black, White & Numbered
18	Black, White & Numbered
19	Black, White & Numbered
20	Black, White & Numbered
21	Black, White & Numbered
22	Black, White & Numbered
23	Black, White & Numbered
24	Black, White & Numbered
25	Black, White & Numbered

Part Number Table

Part#	Gauge	Pairs	Outer Jacket Thickness	Nominal OD over Armor	Outside Diameter Inches	Material Weight (Lbs./M')
T61802P	18	2	.060	.663"	0.763	267
T61804P	18	4	.060	.803"	0.903	405
T61602P	16	2	.045	.693	0.834	295
T61604P	16	4	.060	.866	0.966	498
T61606P	16	6	.060	1.011	1.111	678
T61608P	16	8	.060	1.028	1.128	758
T61612P	16	12	.080	1.241"	1.341	1024
T61624P	16	24	.080	1.577"	1.697	1771

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC