

600V - DURASHEATH, EPR/Hypalon, USE-2 RHH/RHW-2/USE-2-DURASHEATH® EPR Insulation, XL-CPE Jacket 90°C-Single Conductor

Category Conductor Description:

- Tinned copper conductor, Class B stranding

Category Insulation Description:

- Lead-free, Ethylene Propylene rubber (EPR) colored to contrast with Black lead-free XL-CPE Jacket

Category Jacket Description:

- Lead-free, Cross-Linked Chlorinated Polyethylene (XL-CPE)

Applications:

- Ideally suited for use in a broad range of commercial, industrial and utility applications where reliability is a major concern and where maximum performance will be demanded
- In free air, raceways or direct burial
- for use in aerial, conduit, open tray and underground duct/installations

Standards:

- National Electric Code (NEC)
- ICEA S-95-658/NEMA WC70
- "FOR CT USE" on 1/0 AWG and larger in accordance with the NEC
- UL 44 Type RHH/RHW-2
- UL 854 Type USE-2
- UL 1581 VW-1
- IEEE 1202/CSA FT4
- EPA 40 CFR
- OSHA Acceptable
- RoHS Compliant
- UV/Sunlight Resistance

Part Number Table

Part#	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
AF81401	0.03	0.015	0.17	24
AF81201	0.03	0.015	0.19	33
AF81001	0.03	0.015	0.21	48
AF80801	0.045	0.015	0.28	77
AF80601	0.045	0.03	0.35	122
AF80401	0.045	0.03	0.39	178
AF80201	0.045	0.03	0.46	265
AF81/001	0.055	0.045	0.58	422
AF82/001	0.055	0.045	0.63	518
AF83/001	0.055	0.045	0.72	637
AF84/001	0.055	0.045	0.74	785
AF825001	0.065	0.065	0.85	960
AF835001	0.065	0.065	0.96	1299
AF850001	0.065	0.065	1.09	1803
AF875001	0.08	0.065	1.31	2664

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances. * -G represents a Green color code.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC