

## 600V MC CABLE (THHN/THWN-2 Insulation) Solid

### Category Conductor Description:

---

- Plain annealed copper, Concentric-stranded, Class B (ASTM B8), Solid round wire (ASTM B 258)

### Filler:

---

- Non-hygroscopic

### Category Jacket Description:

---

- Nylon

### Category Insulation Description:

---

- THHN/THWN-2 PVC (polyvinyl chloride) with color-coded nylon (polyamide) covering

### Aarmor:

---

- Aluminium tape, Interlock

### Standards:

---

- UL 1569: E38918 UL 83: E15119 ASTM B3 FT4/IEEE 1202 NFPA 70 (National Electrical Code), Article 330 Federal Specification A-A59562

## Part Number Table

Part#	Gauge	Outside Diameter Inches	Insulation Thickness
MC21202-250CL	12	0.475	0.014
MC21202	12	0.475	0.014
MC21402	14	0.43	0.014
MC21402-250CL	14	0.43	0.014
MC21403-250CL	14	0.465	0.014
MC21404	14	0.495	0.014
MC21404-250CL	14	0.495	0.014
MC21403	14	0.465	0.014
MC21203-250CL	12	0.502	0.014
MC21203	12	0.502	0.014
MC21002-250CL	10	0.535	0.02
MC21204	12	0.539	0.02
MC21204-250CL	12	0.539	0.014
MC21002	10	0.535	0.02
MC21003	10	0.58	0.02
MC21003-250CL	10	0.58	0.02
MC21004	10	0.623	0.02
MC21004-250CL	10	0.623	0.02

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC