

## 600 Volts, Copper Conductor Class I Flexible Strand Without Braid CSA Approved, Non-Halogen Insulation 8 AWG through 750 KCMIL – Single Conductor

### Category Conductor Description:

---

- Class I modified bunched (8 and 6 AWG) or rope-bunched (4 AWG and larger) stranded tin-coated copper conforming to ASTM B-33.

### Category Insulation Description:

---

- 90°C / 105°C rated low smoke, non-halogen TelcoHyde® 5266

### Standards:

---

- UL Listed As: Central Office Power Cable
- UL Listed Standard 44: Thermoset Insulated Type RHH/ST1
- FT-4 Flame Test
- VW-1
- ASTM B-33 and B172 for Flexible Strand
- Physical and Electrical tests in accordance with UL

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Stranding</b>	<b>Conductor Diameter</b>	<b>Insulation Min Avg Wall (Mils)</b>	<b>Nominal OD over Insulation</b>	<b>Material Weight (Lbs./M')</b>
TF208-01	8	41/.0201	.153"	60	.274"	78
TF206-01	6	65/.0201	.188"	60	.315"	122
TF204-01	4	105/.0201	.260"	60	.385"	186
TF202-01	2	168/.0201	.305"	60	.430"	256
TF21/0-01	1/0	266/.0201	.392"	80	.560"	434
TF22/0-01	2/0	342/.0201	.455"	80	.620"	533
TF24/0-01	4/0	532/.0201	.577"	80	.745"	832
TF2350-01	350	888/.0201	.760"	95	.960"	1298
TF2500-01	500	1221/.0201	.890"	95	1.090"	1810
TF2750-01	750	1850/.0201	1.094"	110	1.314"	2680

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances. Insert the color number in the XX location: -01 = Black -03 = Red -04 = Green -05 = Blue -06 = Gray TelcoFlex II

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**