

600 Volts, Copper Conductor Single Conductor
Central Office Power Wire and Cable Class I
Flexible Strand With Braid CSA approved,
Non-Halogen Insulation

Telephone and Data Cable

Image Coming Soon

Category Conductor Description:

- Class I modified bunched (8 AND 6 AWG) or rope-bunched (4 AWG and larger) stranded tin-coated copper conforming to ASTM B-33

Category Insulation Description:

- 90°C / 105°C rated limited smoke, non-halogen TelcoHyde® 5221.

Standards:

- UL Listed RHH/ST1
- FT4- Flame Test
- VW-1
- ASTM B-33
- Physical and Electrical tests in accordance with UL standard 44 requirements
- CSA AWM I B 105°C

PART NUMBER TABLE

| Part# | Gauge | Stranding | Conductor Diameter | Insulation Min Avg Wall(Mils) | Nominal OD over Insulation | Nominal OD Overall | Material Weight (Lbs./M') |
|-----------|-------|------------|--------------------|-------------------------------|----------------------------|--------------------|---------------------------|
| TF408-01 | 8 | 41/.0201 | .153" | 60 | .280" | .330" | 95 |
| TF406-01 | 6 | 65/.0201 | .188" | 60 | .315" | .365" | 133 |
| TF404-01 | 4 | 105/.0201 | .260" | 60 | .385" | .435" | 206 |
| TF402-01 | 2 | 168/.0201 | .305" | 60 | .430" | .480" | 293 |
| TF41/0-01 | 1/0 | 266/.0201 | .392" | 80 | .560" | .615" | 449 |
| TF42/0-01 | 2/0 | 342/.0201 | .455" | 80 | .620" | .675" | 554 |
| TF44/0-01 | 4/0 | 532/.0201 | .577" | 80 | .745" | .800" | 807 |
| TF4350-01 | 350 | 888/.0201 | .760" | 95 | .960" | 1.015" | 1304 |
| TF4500-01 | 500 | 1221/.0201 | .890" | 95 | 1.090" | 1.145" | 1765 |
| TF4750-01 | 750 | 1850/.0201 | 1.094" | 110 | 1.320" | 1.380" | 2695 |

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC