

603 - XHHW-2 - 3 Conductor

Aluminum Interlocked Armor
90°C - 600 Volt
Feeder MC, 3-Conductor, Aluminum



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Compact stranded aluminum

Category Assembly Description:

- Insulated conductors are cabled with a bare ground wire, interstices are filled with suitable non-hygroscopic fillers, as required A binder tape of synthetic material assembles the core in an essentially round configuration

Armor:

- Aluminum interlocked armor

Standards:

- UL 1569
- Meets UL 44, XHHW-2 600 V conductors
- Cable Tray Rated

Category Insulation Description:

- Insulated with heat and moisture resistant Cross-linked Polyethylene (XLPE) (type XHHW-2)

Spec Ground:

- Bare compact stranded AA-8000 series aluminum alloy (ACM)

Applications:

- Power lighting, control and signal circuits and as branch circuits and power feeders in industrial, commercial, institutional and residential installations up to 600 volts
- Fished or embedded in plaster and concrete except in damp or wet locations
- Concealed or exposed applications
- Cable trays and other raceways
- Under raised floors of information technology rooms
- Environmental air-handling spaces per NEC Article 300.22 (C)
- Places of Assembly per NEC Article 518.4 and theaters per NEC Article 520.5
- Suitable for use in hazardous locations: Class I and II, Division 2 as well as Class III, Division 1 and 2

- NEC Article 330 (can be messenger supported)
- RoHS Compliant

Part Number Table

Part#	Houston Wire & Cable	Gauge	Conductors	Insulation Thickness	Nominal OD over Armor	Material Weight (Lbs./M')
MCA10603	HW024A06666	6	3	0.045	.776	210
MCA10403	HW024A04446	4	3	0.045	.876	285
MCA10203	HW024A02226	2	3	0.045	1.008	396
MCA10103	HW024A01114	1	3	0.055	1.124	503
MCA11/003	HW024A10134	1/0	3	0.055	1.198	586
MCA12/003	HW024A20134	2/0	3	0.055	1.285	687
MCA13/003	HW024A30134	3/0	3	0.055	1.388	814
MCA14/003	HW024A40132	4/0	3	0.055	1.499	992
MCA125003	HW024A25032	250	3	0.065	1.781	1172
MCA135003	HW024A35032	350	3	0.065	1.859	1521
MCA140003		400	3	0.065	1.951	1709
MCA150003		500	3	0.065	2.248	2249
MCA175003	HW024A75310	750	3	0.08	2.68	3213

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC