

# Flexible and Portable Cord

## 90°C UL/CSA Type SJTOW – 300 Volt

90°C UL/CSA Type SJTOW - 300 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

---

- Stranded Bare copper

### Category Jacket Description:

---

- Gray PVC

### Standards:

---

- UL Flexible Cord – UL Subject 62
- MSHA Approved (where applicable)
- CSA
- RoHS Compliant

### Category Insulation Description:

---

- Premium-grade PVC

### Applications:

---

- Portable tools
- Motors
- Floor maintenance equipment
- Hospital equipment
- Sound equipment
- Washing machines
- Portable lights
- Lamps and similar equipment

Part Number Table

Part#	Gauge	Conductors	Stranding	Outside Diameter Inches	Material Weight (Lbs./M')
BTJ1802-06	18	2	16/30	.290"	42
BTJ1803-06	18	3	16/30	.305"	54
BTJ1603-06	16	3	26/30	.330"	70
BTJ1403-06	14	3	41/30	.365"	92
BTJ1203-06	12	3	65/30	.430"	132

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

Selling Exclusively Through Distribution Since 1977 <sup>TM</sup> | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)  
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •  
St. Louis • Tampa • Toronto  
© 2020 Omni Cable LLC