

Flexible and Portable Cord

90°C UL/CSA Type SJTOW – 300 Volt

90°C UL/CSA Type SJTOW - 300 Volt



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded Bare copper

Category Insulation Description:

- Premium-grade PVC

Category Jacket Description:

- Gray PVC

Applications:

- Portable tools
- Motors
- Floor maintenance equipment
- Hospital equipment
- Sound equipment
- Washing machines
- Portable lights
- Lamps and similar equipment

Standards:

- UL Flexible Cord – UL Subject 62
- MSHA Approved (where applicable)
- CSA
- RoHS Compliant

Color Code Chart	
# of Conductors	Color
1	Black
2	White
3	Green
4	Red
5	Orange
6	Lt Blue

7	White/Black Stripe
8	Red/Black Stripe
9	Green/Black Stripe
10	Orange/Black Stripe
11	Light Blue/Black Stripe
12	Black/White Stripe
13	Red/White Stripe
14	Green/White Stripe
15	Light Blue/White Stripe
16	Black/Red Stripe
17	White/Red Stripe
18	Orange/Red Stripe
19	Light Blue/Red Stripe
20	Red/Green Stripe
21	Orange/Green Stripe
22	Black
23	White
24	Green
25	Red

Part Number Table

Part#	Gauge	Conductors	Stranding	Outside Diameter Inches	Material Weight (Lbs./M')
BTJ1802-06	18	2	16/30	.290"	42
BTJ1803-06	18	3	16/30	.305"	54
BTJ1603-06	16	3	26/30	.330"	70
BTJ1403-06	14	3	41/30	.365"	92
BTJ1203-06	12	3	65/30	.430"	132

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC