

Flexible and Portable Cord

90°C UL/CSA Type SJTOW – 300 Volt

90°C UL/CSA Type SJTOW - 300 Volt



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded Bare copper

Category Insulation Description:

- Premium-grade PVC

Category Jacket Description:

- Gray PVC

Applications:

- Portable tools
- Motors
- Floor maintenance equipment
- Hospital equipment
- Sound equipment
- Washing machines
- Portable lights
- Lamps and similar equipment

Standards:

- UL Flexible Cord – UL Subject 62
- MSHA Approved (where applicable)
- CSA
- RoHS Compliant

Part Number Table

Part#	Gauge	Conductors	Stranding	Outside Diameter Inches	Material Weight (Lbs./M')
BTJ1802-06	18	2	16/30	.290"	42
BTJ1803-06	18	3	16/30	.305"	54
BTJ1603-06	16	3	26/30	.330"	70
BTJ1403-06	14	3	41/30	.365"	92
BTJ1203-06	12	3	65/30	.430"	132

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC