

ALUSE-2-1/0 Aluminum, XLPE Insulated 600V90°C Dry, Wet, Direct Burial



*Product images are for illustrative purposes only and may differ from the actual product.

Part Number Table

Part#	Houston Wire & Cable	Gauge	Insulation Thickness	Outside Diameter Inches
ALUSE-2-6		6	60	0.29
ALUSE-2-4		4	60	0.34
ALUSE-2-2		2	60	0.39
ALUSE-2-1		1	80	0.46
ALUSE-2-1/0	HW003A10101	1/0	80	0.5
ALUSE-2-2/0		2/0	80	0.54
ALUSE-2-3/0		3/0	80	0.59
ALUSE-2-4/0		4/0	80	0.64
ALUSE-2-250		250	95	0.71
ALUSE-2-350		350	95	0.81
ALUSE-2-500		500	95	0.93
ALUSE-2-600		600	110	1.04
ALUSE-2-750		750	110	1.13

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle • St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC