

Aluminum

ALUSE-2-750 Aluminum, XLPE Insulated 600V90°C Dry, Wet, Direct Burial

Part Number Table

| Part# | Gauge | Insulation Thickness | Outside Diameter Inches |
|-------------|-------|----------------------|-------------------------|
| ALUSE-2-6 | 6 | 60 | 0.29 |
| ALUSE-2-4 | 4 | 60 | 0.34 |
| ALUSE-2-2 | 2 | 60 | 0.39 |
| ALUSE-2-1 | 1 | 80 | 0.46 |
| ALUSE-2-1/0 | 1/0 | 80 | 0.5 |
| ALUSE-2-2/0 | 2/0 | 80 | 0.54 |
| ALUSE-2-3/0 | 3/0 | 80 | 0.59 |
| ALUSE-2-4/0 | 4/0 | 80 | 0.64 |
| ALUSE-2-250 | 250 | 95 | 0.71 |
| ALUSE-2-350 | 350 | 95 | 0.81 |
| ALUSE-2-500 | 500 | 95 | 0.93 |
| ALUSE-2-600 | 600 | 110 | 1.04 |
| ALUSE-2-750 | 750 | 110 | 1.13 |

Selling Exclusively Through Distribution Since 1977 [™] | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC