

ALUSE Aluminum, XLPE Insulated 600V90°C Dry, Wet, Direct Burial

Category Conductor Description:

- Compact stranded AA-8000 series aluminum alloy per ASTM B801 or ASTM B836 and ASTM B800

Category Insulation Description:

- Black, thermoset cross-linked polyethylene (XLPE) meeting the requirements of RHH/RHW-2/USE-2 per UL 44 and UL 854

Part Number Table

Part#	Gauge	Insulation Thickness	Outside Diameter Inches
ALUSE-2-6	6	60	0.29
ALUSE-2-4	4	60	0.34
ALUSE-2-2	2	60	0.39
ALUSE-2-1	1	80	0.46
ALUSE-2-1/0	1/0	80	0.5
ALUSE-2-2/0	2/0	80	0.54
ALUSE-2-3/0	3/0	80	0.59
ALUSE-2-4/0	4/0	80	0.64
ALUSE-2-250	250	95	0.71
ALUSE-2-350	350	95	0.81
ALUSE-2-500	500	95	0.93
ALUSE-2-600	600	110	1.04
ALUSE-2-750	750	110	1.13

Selling Exclusively Through Distribution Since 1977 [™] | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC