

Cat5e – Enhanced Category 5E UTP PVC/CMR 350 MHz

Category Conductor Description:

- Solid annealed Bare copper

Category Jacket Description:

- PVC: flame retardant PVC (Polyvinyl Chloride)

Standards:

- ANSI/TIA/EIA 568-A
- FCC PART 68
- ETL/UL Available

Category Insulation Description:

- PVC: polyolefin

Applications:

- 4 Mbps Token Ring (IEEE 802.5)
- 10 Mbps 10 BASE-T ETHERNET (IEEE 802.3)
- 16 Mbps Token Ring (IEEE 802.5)
- 100 Mbps (ANSI X3T9.5 TPDDI)
- 100 VG ANYLAN (IEEE 802.12)
- 100Mbps 100 BASE-T Fast ETHERNET (IEEE 802.3)
- 155 Mbps ATM
- 622 Mbps ATM
- 1000 Mbps 1000 BASE-T Gigabit ETHERNET (IEEE 802.3)

Part Number Table

Part#	Gauge	Pairs	Outside Diameter Inches	Material Weight (Lbs./M')
J462404	24	4	.197"	20
J462404-01	24	4	.197"	20

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC