

Jumper Cable - 5 kV/15kV

Jumper Cable - 5 kV/15kV
Transformer Lead Wire
Non-Shielded - 90°C



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Bare annealed copper

Category Insulation Description:

- EPR per ICEA S-96-659

Applications:

- Used as flexible power lead for temporary connections from phase to phase in voltages from 5 KV to 15 KV

Strand Shield:

- Extruded Semi-Conducting Compound

Category Jacket Description:

- EPDM rubber

Part Number Table

Part#	Gauge	Conductors	Stranding	Nominal OD over Conductor	Outside Diameter Inches	Material Weight (Lbs./M')
B40201	2	1	259	.330	0.82	492
B41/001	1/0	1	259	.420	0.865	580
B42/001	2/0	1	259	.474	0.92	738
B44/001	4/0	1	516	.540	0.985	1017
B435001	350	1	855	.775	0	1487
B450001	500	1	1235	.930	1.395	2087

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com

Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •

St. Louis • Tampa • Toronto

© 2020 Omni Cable LLC