

## Multi-Conductor Shielded, Plenum NEC Type CMP and/or CL3P

Multi-Conductor  
Shielded, Plenum  
NEC Type CMP and/or CL3P



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Stranded or solid bare copper per ASTM B-3, B-8 and B-288

### Shield:

- Overall Flexfoil® polyester supported aluminum foil Stranded tinned copper drain wire

### Applications:

- Power limited control circuits
- Wiring of the following systems:
- Intercom
- Security
- Audio
- Background music
- Suggested Voltage Rating: 300 Volts

### Category Insulation Description:

- Premium-grade, color-coded Flexguard® PVC

### Category Jacket Description:

- Premium-grade natural Flexguard® PVC Sequential footage markings to facilitate installation Temperature range: 0°C to +75°C Ripcord available upon request

### Standards:

- NEC Article 725 Type CL3P (UL: 75°C, 150V)
- NEC Article 800 Type CMP (UL: 75°C, 300V)
- Designed to meet NFPA 262 Flame Test

**Part Number Table**

<b>Part#</b>	<b>Gauge</b>	<b>Conductors</b>	<b>Insulation Thickness</b>	<b>Jacket Thickness</b>	<b>Outside Diameter Inches</b>	<b>Material Weight (Lbs./M')</b>
G111802	18	2	.008"	.015"	.164"	20.5
G111803	18	3	.008"	.015"	.153"	27.5
G111804	18	4	.008"	.015"	.169"	34
G111806	18	6	.010"	.015"	.204"	48.1
G111808	18	8	.010"	.015"	.264"	61
G111810	18	10	.006"	.015"	.264"	5.3
G111812	18	12	.006"	.015"	.273"	86.1
G111602	16	2	.006"	.015"	.154"	28.5
G111603	16	3	.006"	.015"	.190"	28.5
G111604	16	4	.006"	.015"	.181"	49.6

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**