

Non-shielded Stranded Plenum Control Cable, 300V 12 & 14 AWG

Non-shielded Plenum



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper

Category Insulation Description:

- Premium-grade Polyvinyl Chloride (PVC)

Category Jacket Description:

- Premium-grade Polyvinyl Chloride (PVC)

Applications:

- Power limited control circuits
- Wiring of the following systems: Intercom, Security, & Audio
- Suggested Voltage Rating: 300 Volts

Standards:

- NEC Article 725-CL3P, CMP, MPP
- CSA C22.2 No. 214 FT-6 60C

Color Code Chart	
# of Conductors	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray

11	Pink
12	Tan
13	Red/Black Stripe
14	White/Black Stripe
15	Green/Black Stripe
16	Blue/Black Stripe
17	Orange/Black Stripe
18	Yellow/Black Stripe
19	Purple/Black Stripe
20	Gray/Black Stripe
21	Pink/Black Stripe
22	Tan/Black Stripe
23	Black/White Stripe
24	Red/White Stripe
25	Green/White Stripe
26	Blue/White Stripe
27	Brown/White Stripe
28	Orange/White Stripe
29	Yellow/White Stripe
30	Purple/White Stripe

Part Number Table

Part#	Gauge	Conductors	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
G121402	14	2	0.013	0.015	0.216	38.8	57
G121402-07	14	2	0.013	0.015	0.216	38.8	57
G121403	14	3	0.006	0.01	0.232	53.4	79
G121404	14	4	0.006	0.01	0.255	75	111
G121202	12	2	0.011	0.014	0.252	56.5	84

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances * Part Number G121402-07 has an orange jacket

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC