

Security and Alarm Cable

Plenum - 18 AWG - 7x26 & 22 AWG - 7x30 Tinned Copper

Shielded Plenum
200°C FEP - 300 Volt
UL Rated

Category Conductor Description:

- Tinned copper

Category Insulation Description:

- Fluorinated Ethylene Propylene (FEP)

Category Jacket Description:

- 18 AWG - Gray, Fluorinated Ethylene Propylene (FEP) 22 AWG - Red, Fluorinated Ethylene Propylene (FEP)

Applications:

- Audio and control cable
- Alarm and signal use

Standards:

- UL Rated - 80C to 200C
- Voltage: UL 300 Volt
- CMP Rated

| Color Code Chart | |
|------------------|---------------|
| # of Pairs | Color |
| 1 | Red & Black |
| 2 | Green & White |

Part Number Table

| Part# | Gauge | Pairs | Stranding | Insulation Thickness | Jacket Thickness | Outside Diameter Inches | Material Weight (Lbs./M') |
|--------|-------|-------|-----------|----------------------|------------------|-------------------------|---------------------------|
| G52202 | 22 | 2 | 7 x 30 | 0.007 | 0.01 | 0.135 | 18.7 |
| G52203 | 22 | 3 | 7 x 30 | 0.007 | 0.01 | 0.192 | 32.8 |
| G52206 | 22 | 6 | 7 x 30 | 0.007 | 0.012 | 0.288 | 56 |
| G51803 | 18 | 3 | 7 x 26 | 0.006 | 0.012 | 0.291 | 63 |

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977 TM | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC