

Stranded Bare Copper

Stranded Conductor
Bare Copper



*Product images are for illustrative purposes only and may differ from the actual product.

Available In:

- Soft drawn (annealed), medium hard drawn, and hard drawn

Standards:

- REA Approved
- Federal Standard QQ-W-343
- ASTM B-1 (Hard Drawn)
- ASTM B-2 (Medium Hard Drawn)
- ASTM B-3 (Soft or Annealed)
- ASTM B-33 (Tinned Soft or Annealed)

Applications:

- Used in electrical grounding systems and in overhead electrical transmission and distribution systems

Part Number Table

Part#	Gauge	Stranding	Nom O.D. Over Indiv. Wires	Nominal OD Overall	Material Weight (Lbs./M')	Material Weight (KG/KM)
Q11619	16	19	.012"	.059	8	11
Q11407	14	7	.024"	.073	13	19
Q11419	14	19	.015"	.071	12	17
Q11207	12	7	.031"	.092	21	31
Q11219	12	19	.019"	.089	20	29
Q11007	10	7	.039"	.116	33	49
Q11019	10	19	.023"	.116	32	47
Q10807	8	7	.049"	.145	51	75
Q10607	6	7	.061"	.184	81	120
Q10407	4	7	.077"	.232	129	191
Q10207	2	7	.097"	.292	205	305
Q10119	1	19	.066"	.333	261	388
Q11/019	1/0	19	.075"	.374	326	485
Q12/007	2/0	7	.079"	.397	411	611
Q12/019	2/0	19	.084"	.420	411	611
Q13/019	3/0	19	.095"	.470	517	769
Q14/019	4/0	19	.106"	.529	652	970
Q125037	250	37	.082"	.575	772	1148
Q135037	350	37	.097"	.681	1082	1610
Q150037	500	37	.116"	.814	1544	2297
Q175061	750	61	.111"	.998	2319	3451
Q1100061	1000	61	.164"	1.15	3090	4598

Note: The data shown is approximate and subject to standard industry and manufacturer tolerances

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •
St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC