

# Flexible and Portable Cord

## Type SOOW, 10-18 AWG, 2-4 Conductor 600V

Type SOOW - 2-4 Conductor  
EPDM Insulation - CPE Jacket  
90°C - 600 Volt



\*Product images are for illustrative purposes only and may differ from the actual product.

### Category Conductor Description:

- Fully annealed stranded bare copper

### Category Insulation Description:

- Ethylene Propylene Diene Monomer (EPDM)

### Category Jacket Description:

- Chlorinated Polyethylene (CPE)

### Applications:

- Portable tools and equipment
- Portable appliances
- Small motors and associated machinery

### Standards:

- UL Flexible Cord - Subject 62
- MSHA Approved
- CSA C22.2 No. 49

Color Code Chart	
# of Conductors	Color
1	Black
2	White
3	Green
4	Red
5	Orange
6	Lt Blue
7	White/Black Stripe
8	Red/Black Stripe
9	Green/Black Stripe

10	Orange/Black Stripe
11	Light Blue/Black Stripe
12	Black/White Stripe
13	Red/White Stripe
14	Green/White Stripe
15	Light Blue/White Stripe
16	Black/Red Stripe
17	White/Red Stripe
18	Orange/Red Stripe
19	Light Blue/Red Stripe
20	Red/Green Stripe
21	Orange/Green Stripe
22	Black
23	White
24	Green
25	Red

## Part Number Table

Part#	Gauge	Conductors	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)	Filler
B11802	18	2	0.03	0.345	65	96	Jute Rope
B11803	18	3	0.03	0.365	80	119	Jute Rope
B11804	18	4	0.03	0.39	94	139	Jute Rope
B11602	16	2	0.03	0.37	77	114	Jute Rope
B11603	16	3	0.03	0.39	94	139	Jute Rope
B11604	16	4	0.03	0.42	114	169	Jute Rope
B11402	14	2	0.045	0.51	154	229	Jute Rope
B11403	14	3	0.045	0.535	171	254	Jute Rope
B11404	14	4	0.045	0.575	209	311	Jute Rope
B11202	12	2	0.045	0.57	168	250	Jute Rope
B11203	12	3	0.045	0.595	223	331	Jute Rope
B11204	12	4	0.045	0.65	276	410	Jute Rope
B11002	10	2	0.045	0.62	230	342	Jute Rope
B11003	10	3	0.045	0.66	289	430	Jute Rope
B11004	10	4	0.045	0.715	351	522	Jute Rope

Note: The information in this specification sheet is approximate and subject to standard industry and manufacturer tolerances. Please verify specific requirements with your Omni Cable account manager

**Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: [omnicable.com](http://omnicable.com)**  
**Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco • Seattle •**  
**St. Louis • Tampa • Toronto**  
**© 2020 Omni Cable LLC**